

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number  
**WO 2005/054582 A1**

(51) International Patent Classification: **E01F 13/02**  
13/04

(74) Agents: FRY, Alan, Valentine et al.; Fry Heath & Spence  
LLP, The Gables, Massetts Road, Horley, Surrey RH6 7DQ  
(GB).

(21) International Application Number:  
PCT/GB2004/004419

(22) International Filing Date: 20 October 2004 (20.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0325693.0 4 November 2003 (04.11.2003) GB

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GF, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(71) Applicant (for all designated States except US): CORUS  
UK LIMITED [GB/GB]; 30 Millbank, London SW1P  
4WY (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BOWERMAN,  
Hugh, G. [GB/GB]; 39 Horsell Park Close, Woking, Sur-  
reys GU21 4LZ (GB). GIBBS, Lawrence, W. [GB/GB];  
74 Three Elms Road, Hereford HR4 0RJ (GB). TOL-  
LOCZKO, Jurek, J., A. [GB/GB]; 17 Barclay Road,  
Reading RG31 7EW (GB). WHITTON, John, H.  
[GB/GB]; 2 Warwick House Gardens, Askew, Bedale,  
North Yorkshire DL8 1DD (GB). MARSHALL, John,  
R. [GB/GB]; 7 Rimington Gardens, Woodley, Romsey,  
Hampshire SO51 7TT (GB).


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: TRAFFIC CONTROL BARRIERS



(57) Abstract: A traffic control  
barrier comprises at least two  
side-by-side elongate solid blocks  
whose sides are detachably connected  
together by one or more metallic  
connectors. The longitudinal axis  
of the or each connector extends  
in a direction transverse to the  
longitudinal axis of each block and  
in plan view, each block may be  
generally elliptical or rectangular.

WO 2005/054582 A1

## TRAFFIC CONTROL BARRIERS

This invention relates to barriers for controlling the flow of traffic.

Barriers for preventing a vehicle entering a designated area are well known. These barriers typically include, for example, permanent walls and bollards, neither of which are readily deployable. Where deployable barriers are employed, these typically comprise a series of heavy concrete blocks spaced apart by a distance less than the width of a vehicle whose access is to be prevented. These blocks are difficult to transport and manoeuvre in place because of their shape and weight, are unsightly and can often be displaced sufficiently to enable a vehicle to pass.

Safety control barriers for redirecting traffic on, for example, a motorway under repair, also typically comprise a series of individual elongate blocks spaced apart to define one or more sides of a lane to be followed by traffic. Such blocks are typically rectangular in plan view and are, on occasions, connected together at their ends by rods, chains or other similar components.

The present invention sets out to provide traffic control barriers which are more readily transportable and manoeuvrable and which are more efficient in controlling traffic flow than presently available barriers.

In one aspect, the invention provides a traffic control barrier which comprises at least two side-by-side elongate solid blocks each housed within a metallic casing whose sides are detachably connected together by one or more metallic connectors, the longitudinal axis of the or each connector extending in a direction transverse to the longitudinal axis of each block.

In plan view, each block may be generally elliptical or rectangular.

Pads of a compressible material may be positioned below each block. These pads may be positioned at locations at or adjacent to the block ends. Additional pads may be positioned at locations intermediate the block ends. In a preferred embodiment, neighbouring pads are spaced apart such that their total length is less than that of the respective block.

The underside of each block and/or each pad may be formed with a series of ridges or grooves to increase the contact stress between the block and the surface on which it is mounted.

Preferably, the blocks are produced wholly or predominantly from a cementitious material, e.g. concrete. In such an arrangement, the upstanding sides of a concrete block may be housed within a metallic casing. The casing may be produced from, for example, steel or aluminium. One or more metal rods may be welded to opposed internal surfaces of the metallic casing such that the or each rod extends across the width of the casing with its ends secured to the opposed surfaces. The longitudinal axis of the or each welded rod may be substantially normal to the longitudinal axis of the casing. The rods may be welded at their ends to the casing walls by a friction welding technique.

In another aspect, the invention provides a traffic control barrier which comprises at least two side-by-side elongate solid blocks whose sides are detachably connected together by one or more metallic connectors, the longitudinal axis of the or each connector extending in a direction transverse to the longitudinal axis of each block.

In a further aspect, the invention provides a method of producing a dismountable traffic control barrier which comprises transporting to a given site two or more elongate blocks, positioning these blocks side-by-side across an area from which traffic is to be excluded, and securing each

block to the or each neighbouring block by one or more metallic connectors in a detachable manner.

Each block may be produced by casting a cementitious material into an elongate metallic housing whose side walls are interconnected by metallic rods or bars which extend in a direction transverse (e.g. substantially normal) to the longitudinal axis of the housing.

The invention will now be described, by way of example only, with reference to the accompanying diagrammatic drawings in which:-

Figure 1 is a schematic view of a traffic control barrier in accordance with the invention positioned across a road surface;

Figure 2 is a plan view of the upper surface of a block which forms part of the vehicle barrier illustrated in Figure 1;

Figure 3 is a plan view of the under-surface of the block illustrated in Figure 2;

Figure 4 is side view of the block illustrated in Figures 2 and 3; and

Figure 5 is a side view in section of a metallic connector used to connect neighbouring pairs of the blocks illustrated in Figures 1 to 4.

As will be seen from Figure 1, a traffic control barrier in accordance with the invention comprises a plurality of side-by-side elongate concrete blocks 1 spaced apart by a distance significantly less than that of a vehicle whose progress is to be controlled. As shown, the blocks are generally elliptical in plan view and are positioned with their rounded ends directed towards any traffic which may approach the barrier. Thus, an entire roadway or entrance can effectively be sealed off from a flow of traffic by

suitable positioning of the barrier blocks. Other elongate shapes, such as rectangular or diamond, can be adopted for the individual blocks.

As will be seen from Figures 2 to 4, each block comprises a central mass of concrete 2 enveloped in a steel casing 3 formed from steel plates 4, 5. Rigid steel bars 6 extend between the inner surfaces of the plates 4, 5 with their ends welded to the plates by, for example, a friction welding technique. At their side edges, the plates are welded to upstanding metal tubes 7 to define the generally elliptical shaping for the blocks.

Open ended tubes 8 extend through the blocks with their open ends projecting a small distance from the casing outer surface. These open ends may be selectively closed by suitably dimensioned removable caps (not shown). Lifting hoops 9 (see Figure 4) project from the upper surface of each block to assist manoeuvring and positioning of the blocks in use. Each lifting hoop includes an anchorage 11 embedded in the concrete mass.

As will be seen from Figure 3, ribbed rubber pads 12 are secured to the under-surface of each block to increase the contact stress between the blocks and the road surface on which it is mounted. The undersurface of the pads may comprise a material having a high coefficient of friction and the pads 12 preferably extend over the full width of the block under-surface and are positioned towards each block end. Additional pads may be provided.

Manufacture of the blocks is achieved by friction welding the steel bars 6 to the inner surface of each steel plate 4, 5 and welding the plate ends to the metal tubes 7. The tubes 8 are positioned between suitably dimensioned openings formed in the plate surfaces and the entire central area of each block is filled with concrete. Prior to casting of the concrete, the lifting hoop anchorages 11 are positioned as shown in Figure 2. Once the concrete is set, the ribbed pads 12 are secured to the under-surface of

each block and each lifting hoop 9 fitted to its anchorage. For additional weight, iron ingots or the like may be positioned within the casing before casting of the concrete.

Typically, the height of each block is between 800 and 1000mm with the tubes 8 positioned approximately at mid-height of the plates 4, 5. The length of each block is typically between 2000mm and 4000mm and the maximum width of each block is typically between 450 and 650mm.

Connectors for detachably joining the blocks together are illustrated in Figure 5. These connectors include the metal tubes 8 which are embedded within the concrete mass of the blocks. Each tube 8 has a bore for receiving one or a series of connector rods 15. Each rod is formed at its ends with external threads to receive an internally threaded tubular end-piece 16 positioned one at each end of a metallic connecting member 17. The connector rod 15 extends within the metal tube 8 by a distance of at least 1.5 x tube internal diameter. Flats may be formed on each connecting member to assist the connection procedure.

When a traffic control barrier is required, several blocks are transported to site and off-loaded from the carrying vehicle using a conventional lifting device which cooperates with the hoops 9. As a block is positioned, one or a series of threaded rods 15 are inserted into the bore of the block and the female end of a connecting member 16 is secured to the exposed end of the outermost threaded rod. A second block is then positioned close to the first block and the other female end of the connecting member is secured to the bore mounted threaded rod of that block. This process is repeated until the entire road section to which traffic access is to be refused is covered. To remove the barrier, this process is repeated in reverse.

It will be appreciated that the foregoing is merely exemplary of traffic control barriers in accordance with the invention and that

modifications can readily be made thereto without departing from the scope of the invention as set out in the accompanying claims.

CLAIMS

1. A traffic control barrier which comprises at least two side-by-side elongate solid blocks each housed within a metallic casing whose sides are detachably connected together by one or more metallic connectors, the longitudinal axis of the or each connector extending in a direction transverse to the longitudinal axis of each block.
2. A barrier as claimed in claim 1 wherein the metallic connectors wherein the metallic connectors are rigid.
3. A barrier as claimed in claim 1 or claim 2 wherein in plan view, each block is generally elliptical or rectangular.
4. A barrier as claimed in any one of claims 1 to 3 wherein pads of a compressible material are positioned below each block.
5. A barrier as claimed in claim 4 wherein the undersurface of each pad has a relatively high coefficient of friction.
6. A barrier as claimed in claim 4 or claim 5 wherein the pads are positioned at locations at or adjacent to the block ends.
7. A barrier as claimed in any one of claims 4 to 6 wherein additional pads are positioned at locations intermediate the block ends.
8. A barrier as claimed in any one of claims 4 to 7 wherein neighbouring pads are spaced apart such that their total length is less than that of the respective block.
9. A barrier as claimed in any one of the preceding claims wherein the underside of each block and/or each pad is formed with a series of



ridges or grooves to increase the contact stress between the block and the surface on which it is mounted.

10. A barrier as claimed in any one of the preceding claims wherein the blocks are produced wholly or predominantly from a cementitious material.
11. A barrier as claimed in any one of the preceding claims wherein one or more metal rods are welded to opposed internal surfaces of the metallic casing such that the or each rod extends across the width of the casing with its ends secured to the opposed surfaces.
12. A barrier as claimed in claim 11 wherein the longitudinal axis of the or each welded rod is substantially normal to the longitudinal axis of the casing.
13. A barrier as claimed in claim 11 or claim 13 wherein the rods are welded at their ends to the casing walls by a friction welding technique.
14. A traffic control barrier which comprises at least two side-by-side elongate solid blocks whose sides are detachably connected together by one or more metallic connectors, the longitudinal axis of the or each connector extending in a direction transverse to the longitudinal axis of each block.
15. A method of producing a dismountable traffic control barrier which comprises transporting to a given site two or more elongate blocks each produced by casting a cementitious material into an elongate metallic housing whose side walls are interconnected by metallic rods or bars which extend in a direction transverse to the longitudinal axis of the housing, positioning these blocks side-by-side across an area from which traffic is to be excluded, and

securing each block to the or each neighbouring block by one or more metallic connectors in a detachable manner.

1/2

FIG. 1




FIG. 2





FIG. 3



SUBSTITUTE SHEET (RULE 26)

2/2

FIG. 4





FIG. 5



SUBSTITUTE SHEET (RULE 26)

## INTERNATIONAL SEARCH REPORT

 Int. Application No.  
 PC1/GB2004/004419

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 E01F13/02 E01F13/04		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 E01F		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 990 736 A (PEREIRA CARLOS) 5 April 2000 (2000-04-05) paragraph '0012! - paragraph '0032!; figures 1,2,4	1-6, 12, 14
P, X	FR 2 841 267 A (FERRARI ROLAND) 26 December 2003 (2003-12-26) page 2, paragraph 2 - page 4, paragraph 3; figures 1,2	1, 3, 9, 10, 14
P, A	EP 1 441 071 A (CORUS UK LTD) 23 July 2004 (2004-07-28) the whole document	1-15
<input type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "Z" document member of the same patent family		
Date of the actual completion of the international search 25 November 2004		Date of mailing of the international search report 03/02/2005
Name and mailing address of the ISA European Patent Office, P.O. 5010 Patenlaan 2 NL - 2204 HW Rijswijk Tel (+31-70) 340-2010, Tx: 31 651 epo nl Fax (+31-70) 340-9010		Authorized officer Geiger, H

Form PCT/ISA/210 (second sheet) (January 2004)

# INTERNATIONAL SEARCH REPORT

information on patent family members

Int'l Application No  
P 682004/004419

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0990736	A	05-04-2000	FR EP 2784126 A1 0990736 A1	07-04-2000 05-04-2000
FR 2841267	A	26-12-2003	FR 2841267 A1	26-12-2003
EP 1441071	A	28-07-2004	GB EP EP GB 2397604 A 1441071 A2 1441072 A2 2397605 A	28-07-2004 28-07-2004 28-07-2004 28-07-2004

Form PCT/ISA/E10 (patent family annex) (January 2004)